



Stock and Standard (Non-Stock) Finned Aluminum Cast-In Band Heaters for Extrusion Processing

➤ **Standard Sizes and Ratings Listed by Extruder Size**

➤ **These Sizes and Ratings are among the most commonly used. They will provide the shortest delivery times.**

Stock Items Are Shown In RED

I.D. in	O.D. in	Length in	Material	Watts Each Half	Volts Each Half	Phase	Termination Type	Clamping Type	Heater End Type (pg 3-44)	Cast-In Heater Part Number
2.25	4	5.5	Bronze	600	230	1	R	Bolt	FS2	CBH12388
3	4.75	7.5	Bronze	1000	230	1	R	Bolt	FS2	CBH12387
3.75	8	9.875	Alum 319	1350	207	1	S	Bolt	FS2	CBH10404
4	8	8.75	Alum 443	2000	230	1	S	Strap	FS1	CBH09461
4	8	9	Alum 319	1500	230	1	S	Strap	FS1	CBH08712
4	8	11	Alum 319	1850	230	1	S	Strap	FS1	CBH08713
4.375	8.25	12.25	Alum 319	2000	230	1	R	Strap	FS1	CBH01139
4.5	8.25	12.5	Alum 319	2500	190	1	C4	Bolt	FS2	CBH14634
4.5	8.5	12	Alum 319	2750	240	1	R	Bolt	FS2	CBH06640
4.5	8.5	12	Alum 319	2750	200	1	R	Bolt	FS2	CBH08651
4.5	9	11.5	Alum 319	2000	230	1	S	Strap	FS1	CBH05533
4.921	8.421	9	Bronze	2500	480	3	C4	Strap	FS1	CBH08576
4.922	7.5	5.906	Alum 319	1630	230	1	T7	Bolt	FS2	CBH10044
4.922	7.5	7.087	Alum 319	2180	230	1	T7	Bolt	FS2	CBH10045
5	7.75	12.75	Alum 319	2625	200	1	R	Bolt	FS2	CBH11859
5	9	13	Alum 319	2750	240	1	S	Strap	FS1	CBH12840
5.002	9.25	12.25	Alum 319	2000	240	1	T	Strap	FS1	CBH03319
5.5	8.75	12.5	Alum 319	2800	600	1	S	Bolt	FS1	CBH07945
5.5	8.75	12.5	Alum 319	2800	460	1	S	Bolt	FS1	CBH07952
5.5	8.75	12.5	Alum 319	2800	240	1	S	Bolt	FS1	CBH10362
5.5	9.5	12	Alum 319	2300	240	1	S	Strap	FS1	CBH06724
5.5	9.5	12.5	Alum 319	2800	240	1	S	Bolt	FS2	CBH04982
5.5	9.5	12.5	Alum 319	2800	415	1	S	Bolt	FS2	CBH12906
6	10.5	11.5	Alum 319	2700	230	1	S	Strap	FS1	CBH02588
6	10.5	14.5	Alum 319	3500	230	1	T7	Strap	FS1	CBH02432
6.25	10.25	6.25	Alum 319	1400	200	1	S	Bolt	FS2	CBH08653
6.25	10.25	6.25	Alum 319	1700	240	1	R	Bolt	FS2	CBH06373
6.25	10.25	13.688	Alum 319	3000	230	1	R	Strap	FS2	CBH01406
6.25	10.25	17.75	Alum 319	5800	240	1	R	Bolt	FS2	CBH06623
6.25	11.25	15.875	Alum 319	5000	230	1	S	Bolt	FS1	CBH03365
6.3	9.55	15.75	Alum 319	5000	240	1	C4	Strap	FS1	CBH03793
6.3	9.55	15.75	Alum 319	5000	380	1	S	Strap	FS1	CBH11795
6.3	10.05	15.75	Alum 319	5000	380	1	S	Bolt	FS1	CBH12907
6.3	10.05	15.75	Alum 319	5000	415	1	S	Bolt	FS1	CBH12908
6.3	10.05	15.75	Alum 319	5000	440	1	S	Bolt	FS1	CBH12668
6.5	9.5	15	Alum 319	3250	230	1	T7	Bolt	FS1	CBH14207
6.5	9.5	17.5	Alum 356	3400	230	1	T	Bolt	FS2	CBH07553
6.5	10.5	13	Alum 319	4300	230	1	E	Bolt	FS2	CBH09631
6.5	10.5	13	Alum 319	4300	190	1	E	Bolt	FS2	CBH09424
6.6	10.625	14.75	Alum 319	3250	240	1	S	Strap	FS1	CBH07649
6.625	9.875	18	Alum 319	4400	600	1	S	Bolt	FS1	CBH07946
7	10.25	18	Alum 319	6000	290	3	E	Strap	FS2	CBH09420
7.5	11	16.5	Bronze	5100	230	1	R	Strap	FS2	CBH11105
7.5	11.25	19	Alum 319	8000	380	1	S	Bolt	FS1	CBH12447

Key for Abbreviations found under the Termination Column

- | | |
|---|---|
| C4 = Screw Terminal with Ceramic Cover | R1A = Stainless Steel Wire Overbraid |
| E = Right-Angle Lug | R2 = Blockhead Screw Terminal |
| F = Flexible Lead Wire | S = Screw Terminal with Heavy Duty Ceramic Insulator |
| R = 90° Blockhead Screw Terminal | T = Screw Terminal with Mica Insulator |
| R1 = Flexible Armor Cable | T7 = Screw Terminal with Ceramic Insulator |

CONTINUED ➤