

Non-contact Thermometers — Portable

Beam-A-Temp™ Wide Range Infrared Thermometer with Type K input

Measures both non-contact and contact temperature with type K thermocouple input



Design Features

- * Wide temperature range for IR temperature and type K thermocouple instruments.
- * Automatic emissivity adjustment (for temperatures 212°F or higher).
- * Memory stores up to 20 readings.
- * Large LCD display with bright backligh for easy-to-read measurements and program, ing parameters.
- * Laser pointer provides better aim an accur. v.
- * Auto-hold activates when the consument to get is released.
- * Adjustable high/low as ym that's user visually and audibly when temperature exce. Is placed med limits.
- * MAX/MIN/4VG/AVF features display highest, lowest, average, nav (AX) in MIN values.
- * Deta H. V. Auto Power Off, and low battery indication.
- Swidges by it into handle allow for °C/°F display selection, auto power off defeat, and alarm on/off control.
- * Cyclete with 9V battery, type K thermocouple sensor (-4 to 482°F/-20 to 250°C), and carrying case.
- * 1-year warranty.

Specifications_

Display Counts: 20 court backlit of play

Range: Infra d: -. . to 1+/2°F (-50 to 800°C) Type 1 -58 b 2498°F (-50 to 1370°C)

with other Type K miniature connect

measurements up

for higher

Basic Accuracy Infrar a: $\pm 2\%$ of reading or $\pm 4^{\circ}\text{F/2}^{\circ}\text{C}$

Typ: A: (±1.5% of reading +2°F/1°C)

Maximum Resolution: 0.1°F/°C


Emissivity: Adjustable 0.10 to 1.00 **Field of View:** 13:1 distance to target ratio

Dimensions: $3.2 \times 1.6 \times 6.3$ " (82 × 42 × 160 mm)

Weight: 6.4 oz. (180g)

Agency Approval:





13:1 distance to target ratio

Ordering Information

Part Number **REB30020** Wide Range IR Thermometer + Type K Part Number **REB32020** Wide Range IR Thermometer with NIST Certificate

Standard lead time is stock to 3 weeks.

▲ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.